

**Amendments to the Specification**

Please replace paragraph [0014] with the following rewritten paragraph:

FIG. 5 is a sectional top view of a water driven turbine as viewed along line A-A 5-5 in FIG. 6.

Please replace paragraph [0015] with the following rewritten paragraph:

FIG. 6 is a sectional side view of the water driven turbine as viewed along line B-B 6-6 in FIG. 5.

Please replace paragraph [0017] with the following rewritten paragraph:

FIG. 8 is a sectional view of the showerhead (with the water distribution plate removed) as viewed from line C-C 8/9-8/9 in FIG. 7.

Please replace paragraph [0018] with the following rewritten paragraph:

FIG. 9 is a sectional view of the showerhead (with the water distribution plate installed) as viewed from line C-C 8/9-8/9 in FIG. 7.

Please replace paragraph [0031] with the following rewritten paragraph:

Fig. 8 is a sectional view of the showerhead 100 (with the water distribution plate 106 removed) as viewed from line C-C 8/9-8/9 in FIG 7, and FIG 9 is a sectional view of the showerhead 100 (with the water distribution plate 106 installed) as viewed from line C-C 8/9-8/9 in FIG 7. In accordance with one practical embodiment, the showerhead 100 is formed by coupling the water distribution element 106 to a main body portion 124 of the showerhead 100 as shown in FIG. 9. The lighting element is positioned within or on top of the showerhead 110 so that the one or more lights 154 shine through the translucent material of the distribution element 106 and main body portion 124.